


TWN4 MultiTech 2 M LF HF

Multi-frequency RFID module (LF/HF) with NFC support



TWN4 MultiTech 2 M LF HF
(exemplary illustrations)

The TWN4 MultiTech 2 family of contactless RFID readers and modules allows users to read and write to almost any LF and HF tags and labels. All products support NFC and, optionally, Bluetooth Low Energy (BLE). In addition, they are also compatible with the two most commonly used smartphone operating systems, Android and iOS, which gives the option to integrate them in mobile identification applications. The desktop readers are available as Plug & Play devices that can be easily customized (i.e. inlay design), whereas the PCB modules offer a large amount of interfaces and a perfect form factor for an easy and quick integration in any host device. This broad range of product features makes the TWN4 MultiTech 2 family an excellent solution for almost every project.

Key features of the TWN4 MultiTech 2 M LF HF RFID module include a powerful SDK for writing apps that are executed directly on the module, the possibility to upgrade the firmware in the field, and transparent data exchange with the RFID media. Additionally, the module can read more than 60 RFID technologies from low (LF) and high frequency (HF) bands, including NFC. This gives the option to select as many of the technologies required instead of being forced to select just a few ones.

Special features:

- + Possibility to read more than 60 RFID technologies
- + Two RFID frequencies (125 kHz/13.56 MHz) and NFC support
- + Powerful SDK for writing apps which are executed directly on the module
- + Firmware update in the field possible
- + On-board 18 kB flash storage, e.g. for storing user accessible non-volatile data
- + Supports transparent data exchange with RFID media
- + CCID and PC/SC 2.01
- + Compact form factor for easy integration



Elevator



EV Chargers



Access



Shop POS



Fitness
Equipment



Ticket POS



PC Log-on



Document
Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time
Attendance



Industrial
PC

TECHNICAL DATA

| | |
|------------------------------------|---|
| FREQUENCIES | 125 kHz (LF) / 13.56 MHz (HF) |
| ANTENNAS | Integrated |
| DIMENSIONS (L X W X H) | Approx. 76.00 x 49.00 x 8.20 mm / 2.99 x 1.93 x 0.32 inch |
| POWER | USB: 4.3 V - 5.5 V Generic interface (X1): 3.3 V ± 5% RS-232: requires 5 V external power supply PS2 classified power source according to IEC 62368-1, short-circuit current < 8 A |
| POWER OUTPUT | 125 kHz: -9.95 dbμA/m at 10 meters 13.56 MHz: -2.25 dbμA/m at 10 meters |
| MODULATION | ASK / ASK |
| CURRENT CONSUMPTION | RF field on: 120 mA typically / Sleep: 500 μA typ. |
| TEMPERATURE RANGE | Operating: -25 °C up to +80 °C (-13 °F up to +176 °F) Storage: -40 °C up to +85 °C (-40 °F up to +185 °F) |
| RELATIVE HUMIDITY | 5% to 95% non-condensing |
| READ/WRITE DISTANCE | LF and HF: up to 100 mm / 4 inch, depending on environment and transponder |
| OPERATING MODES (USB) | USB keyboard emulation – USB virtual COM port – CCID / PC/SC 2.01 |
| MTBF | 500,000 hours |
| WEIGHT | Approx. 10 g / 0.35 oz (without cable) |
| SUPPORTED OPTIONS AND TRANSPONDERS | Depending on the firmware version and installed options, ELATEC readers and modules can support a wide range of RFID technologies. Please refer to the relevant ELATEC transponder matrix (available at www.elatec-rfid.com/int/transponder-technology) for more information about the available options and RFID technologies supported by the product. |
| OS SUPPORT | Windows 7 (32-/64-bit) and higher versions, Linux, Android ¹⁾ , iOS ¹⁾ , MAC OS X ¹⁾ |
| PERIPHERAL INTERFACES | USB, RS-232, TTL serial (logic level 3.3 V, CMOS, 5 V tolerant), I ² C, 4 GPIOs, Clock/Data, Wiegand D0/D1, 2 SAM slots for ID-000 card format |
| TRANSMISSION SPEED | Host: USB full speed (12 Mbit/s), RS-232: up to 115,200 baud, HF Air: up to 848 kbit/s |
| CERTIFICATION NAME | TWN4 MultiTech 2 M LF HF |
| CERTIFICATIONS | Non-exhaustive list ²⁾ : CE/RED, FCC, IC, REACH and RoHS-III compliant |
| ORDER CODES | T4BO-F6 Standard reader module T4BO-F6-P Reader module with P option T4BO-F6-PI Reader module with PI options |


¹⁾On request

²⁾The product has been certified for use in many countries and regions. Contact your Sales representative for detailed information about all certifications and approvals granted to the product.

ACCESSORIES

| | |
|---------------------------|--|
| CABLES AND POWER SUPPLIES | ELATEC RFID readers and modules can be delivered with additional cables or external power supplies. Refer to the data sheet <i>Cables for ELATEC devices</i> for detailed information. |
|---------------------------|--|

TECHNICAL DRAWINGS



All measures in mm [inch]

ELATEC GmbH
 Zeppelinstr. 1
 82178 Puchheim
 Germany
 P +49 89 552 9961 0
 F +49 89 552 9961 129
 E-Mail: info-rfid@elatec.com
 Website: elatec.com

ELATEC Systems GmbH
 Schwieberdinger Str. 44
 71636 Ludwigsburg
 Germany
 P +49 7141 309736 0
 E-Mail: info-rfid@elatec.com
 Website: elatec.com

ELATEC Inc.
 1995 SW Martin Hwy
 Palm City • FL 34990
 USA
 P +1 772 210 2263
 F +1 772 382 3749
 E-Mail: americas-info@elatec.com
 Website: elatec.com

ELATEC Technology (Shenzhen) LLC
 918, Main Building, Tian An Cyber Times
 Tower, No. 6, Tairan Fourth Road, Tian 'an
 Community, Shatou Neighborhood
 Futian District • Shenzhen • China
 P/F +86 755 2394 6014
 E-Mail: apac-info@elatec.com
 Website: elatec.com

ELATEC reserves the right to change any information or data in this document without prior notice. ELATEC declines all responsibility for the use of this product with any other specification but the one mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names used in this document are registered trademarks of their respective owners.