

Dual ISO CF Card Reader 14443A / 14443B



The Dual ISO CF Card Module is a highly integrated contact less short range read write device that, with its interoperability capability, supports the whole MIFARE® family, ISO14443A and ISO14443B RFID devices. The module has a built in antenna. It fits into CF card slots and via an adapter also into PCMCIA slots of any kind of mobile device. The integrated technology enables a state of the art security level. This RFID read / write unit is optimized for maximum data throughput rates on both, the air interface as well as the serial interface. The built in boot-loader enables firmware field upgrades via the serial interface.

Technical Data

RF Transmit Frequency	13.56MHz		
Supported Standards	ISO14443A, ISO14443B		
Supported Tag-ICs	MIFARE® Standard MIFARE® 4k MIFARE® ProX MIFARE® Ultralight MIFARE® DESFIRE SmartMX	SLE 55Rxx SLE 66CL160S SLE 66CLX320P SR176 SRIX4K	ISO14443A Tags ISO14443B Tags Jewel Tag (IRT0302B11 KSW DIY Eng. Sample) Sharp B ASK GTML2ISO TOSMART P064
Communications Interface	CF Card Interface		
Communications Protocol	Specific ASCII or Binary Protocol		
Communications Parameter	9600 Bit/s to 115kBit/s, 8, n, 1		
Firmware Boot-Loader	Yes		
SW Driver	Not required		
Power Supply	Via CF Card Interface		
Current Consumption	Typ. 200mA in active mode max. 310 mA <65 mA Antenna off <1µA in disconnected mode		
Reading distance	Up to 60 mm / 2,36 Inch, depending on tag		
RF Transmission Speed	Up to 848 kBit/s		
Antenna	Integrated		
Size	(LxWxH) 43.0x84.0x7.0mm / 1.69x3.31x0.02Inch		
Weight	21g ± 10% / 0.046 lb ± 10%		
Operating Temperature	0°C to +70°C / +32F to +158F		
Storage Temperature	-20°C to +85°C / -4F to +185F		
Approvals	EN 300-330, CE		
Order code	AXB811		

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems
Max-Planck-Str. 16, D-82223 Eichenau, GERMANY
Phone: +49 8141 53498-0
Fax: +49 8141 53498-29
RFID@elatec.de

Elatec Vertriebs GmbH
Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY
Phone: +49 89 46 23 070 ;
Fax: +49 89 460 24 03
info@elatec.de