

## HF Mifare Easy Compact Plug & Play Module



The HF Mifare Easy Compact Plug & Play Module is a contact less proximity read/write device that supports various RFID-devices out of the MIFARE® family and the ISO 14443 A standard. The module comes with an integrated and optimized antenna for a quick and easy integration into applications. By using the serial interface the device can be connected to a controller or any host system easily. The form factor enables a design in even into very compact systems.

### Technical Data

RF Transmit Frequency	13.56MHz		
Supported Standards	ISO14443A		
Supported Tag-ICs	MIFARE® Standard MIFARE® 4k MIFARE® Pro X MIFARE® Ultralight MIFARE® DESFire (Serial No. only)	SLE66R35 SLE44R35	ISO 14443A Tags
Host Communication	Point-to-Point		
Communications Interface	RS232 Serial Interface		
Communications Protocol	Specific ASCII and Binary Protocol		
Communications Parameter	9600 Bit/s to 57600 Bit/s, 8, N, 1		
Firmware Boot-Loader	no		
Software, Driver	API - DLL		
Power Supply	5VDC ± 10% regulated		
Current Consumption	150 mA < 10mA at power down mode		
Reading distance	Up to 85mm, depending on tag and antenna		
RF Transmission Speed	106 kBit/s		
Antenna	Integrated		
Input / Output Connector	Bidirectional Read indicator LED, 1 I/O Port		
Size	(LxWxH) 70.0x45.0x12.1mm ± 1.0mm / 2.76x1.77x0.48 Inch ± 0.04 Inch		
Weight	16g ± 10% / 0.04 lb± 10%		
Operating Temperature	-20°C to + 80°C / -4F to +176 F		
Storage Temperature	-40°C to + 85°C / -40F to +185F		
Approvals / Compliances	EN 300-330, CE, FCC Part 15, RoHS compliant		
Order code	AXC021		

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems  
Max-Planck-Str. 16, D-82223 Eichenau, GERMANY  
Phone: +49 8141 53498-0  
Fax: +49 8141 53498-29  
RFID@elatec.de

Elatec Vertriebs GmbH  
Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY  
Phone: +49 89 46 23 070 ;  
Fax: +49 89 460 24 03  
info@elatec.de