

### HF Multi ISO Compact Plug & Play Module



The HF Multi ISO Compact Plug & Play Module is a contact less proximity read/write device that supports various ISO 14443A/B, ISO 15693, ISO 18000-3 and EPC RFID-devices, including the whole MIFARE® family. The module has a built in antenna. By using the RS232 interface the device can be connected to a PC or any other host system easily. An integrated SAM Socket enables a state of the art security level. This RFID read/write unit is optimized for maximum data throughput rates on both, the air interface as well as the serial interface. The built in boot-loader enables firmware field upgrades via the serial interface.

#### Technical Data

RF Transmit Frequency	13.56MHz		
Supported Standards	ISO 14443A, ISO 14443B, ISO 15693, ISO 18000-3, ICODE		
Supported Tag-ICs	MIFARE® Standard	SLE 55Rxx	Tag-it HF-I
	MIFARE® 4k	SRF55VxxP +S	Tag-it HF-I Light S
	MIFARE® Pro X	SLE 66CL160S	Jewel Tag
	MIFARE® Ultralight	SLE 66CLX320P	(IRT0302B11 KSW
	MIFARE® DESFIRE	SR176	DIY Eng. Sample)
	MIFARE® SmartMX	SRIX4K	Sharp B
	I-CODE SLI (SL2ICS20)	LRI 12	ASK GTML
	I-CODE EPC (SL2ICS10)	LRI 64	ASK GTML2ISO
	I-CODE UID (SL2ICS11)	LRI 512	TOSMART P064
	I-CODE	EM4135	ISO14443A/B Tags
		KSW Temp Sense	ISO15693 Tags
Host Communication	Point-to-Point		
Communications Interface	RS232		
Communications Protocol	Specific ASCII or Binary Protocol		
Communications Param.	9600 Bit/s to 115 kBit/s, 8,N,1		
Firmware Boot-Loader	Supported Via Serial Interface		
SW Driver	Virt. COM port Driver, API - DLL (VC++), PC/SC Driver for MS Win 2000/XP (for Mifare and 14443-4 only)		
Power Supply	5V DC ± 10% regulated		
Current Consumption	150 mA < 10mA at power down mode		
Reading distance	Up to 85mm, depending on tag and antenna		
RF Transmission Speed	up to 848 kBit/s		
Antenna	Integrated		
Input / Output Connector	Read indicator LED, 1 I/O Port, SAM Socket		
Size (LxWxH)	70.0x45.0x12.1mm ± 1.0mm / 2.76x1.77x0.48 Inch ± 0.04 Inch		
Weight	17g ± 10% / 0.04 lb± 10%		
Operating Temperature	-20°C to + 80°C / -4F to +176 F		
Storage Temperature	-40°C to + 85°C / -40F to +185F		
Approvals	ETS 300-330, CE, FCC pending		
Order Code	AXC321		

Datenblatt Datasheet

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems  
 Max-Planck-Str. 16, D-82223 Eichenau, GERMANY  
 Phone: +49 8141 53498-0  
 Fax: +49 8141 53498-29  
 RFID@elatec.de

Elatec Vertriebs GmbH  
 Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY  
 Phone: +49 89 46 23 070 ;  
 Fax: +49 89 460 24 03  
 info@elatec.de