

2.45GHz Network Reader



Technical data

Communication	2.45 GHz Support read and write
Frequency	2.40~2.48 GHz
Channel	255
Address	65536
RSSI	0-255
LQI	0-255
Programmable	Set Parameter
LED	Multi-LED visual indication
Ethernet	10/100 base-T Ethernet (RJ-45)
RS-232	RX, TX
Protocols	ICMP, ARP, IP, TCP(Server/Client), UDP, DHCP,
Baud Rate	2,400 bps ~ 115,200 bps
Power Input	7.5 VDC ~ 28 VDC
Action Current	MAX 500 mA @ 9 VDC
Operating Temperature	-20 °C to 65 °C, 5 to 95%RH
Storage Temperature	-30 °C to 85 °C, 5 to 95%RH
Dimension	107W x 138H x 30D (mm)
Order Code	SYRD245-1N

Datenblatt Datasheet

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems
 Max-Planck-Str. 16, D-82223 Eichenau, GERMANY
 Phone: +49 8141 53498-0
 Fax: +49 8141 53498-29
 RFID@elatec.de

Elatec Vertriebs GmbH
 Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY
 Phone: +49 89 46 23 070 ;
 Fax: +49 89 460 24 03
 info@elatec.de