

PU Coin



Mechanical dimensions	Diameter	Thickness mm	Hole
	34 mm +/- 0.5mm	8mm +/- 0.3mm	5.5 mm +/-0.3mm
Chip type	EM4100		
Electrical	Operating frequency	125kHz +/- 6kHz	
Temperature	Operating	-25°C to + 85°C	
Material	PVC (housing), Epoxy (cast integral)		
Options	Color: Red, Yellow, Blue		
Type number	TG-4100-PU-C (C= colour)		

Datenblatt Datasheet

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems
 Max-Planck-Str. 16, D-82223 Eichenau, GERMANY
 Phone: +49 8141 53498-0
 Fax: +49 8141 53498-29
RFID@elatec.de

Elatec Vertriebs GmbH
 Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY
 Phone: +49 89 46 23 070 ;
 Fax: +49 89 460 24 03
info@elatec.de