

## Leather Key Fob



Mechanical dimensions	Dimension mm	Thickness mm	
	Customizable dimension	≥3.5mm	
Chip type	EM series, Atmel series, Hitag series, Mifare series, I-code series		
Electrical	LF Operating frequency	125kHz*	+/- 6kHz
	HF Operating frequency	13.56MHz Reader Standard	ISO/IEC 15693 ISO/IEC 14443
Temperature	Storage	-25°C to +75°C	
	Operating	-25°C to + 75°C	
Material	Genuine leather, copper wire antenna and IC module		
Enclosure rating	IP65		
Options	Customizable colours, Metal key ring, 1 or 2 side logo printing, sear logo		
Packaging	Delivered in bubble pack tube and packed in a box		
Type number	LKF - XX (Keyfob, XX denotes IC) LKFR -XX (Keyfob with ring, XX denotes IC)		

Datenblatt Datasheet

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, IDentification Systems  
 Max-Planck-Str. 16, D-82223 Eichenau, GERMANY  
 Phone: +49 8141 53498-0  
 Fax: +49 8141 53498-29  
[RFID@elatec.de](mailto:RFID@elatec.de)

Elatec Vertriebs GmbH  
 Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY  
 Phone: +49 89 46 23 070 ;  
 Fax: +49 89 460 24 03  
[info@elatec.de](mailto:info@elatec.de)