

2.45GHz CF Card Reader



Technical data

Frequency	2.40 – 2.48 GHz
Interface	CF Type 1
Read range	Up to 16m
Optical feedback	Multi-LED visual indication
Operating system	PDA Pocket PC 2003 / Windows mobile 5.0
Action current	Max. 50mA @3.3V DC
Operating temperature	-20°C - +65°C at 5-95% RH
Storage temperature	-30°C - +85°C at 5-95% RH
Dimensions (W * L * H)	42,7 * 55,3 * 6,24 mm

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems
Max-Planck-Str. 16, D-82223 Eichenau, GERMANY
Phone: +49 8141 53498-0
Fax: +49 8141 53498-29
RFID@elatec.de

Elatec Vertriebs GmbH
Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY
Phone: +49 89 46 23 070 ;
Fax: +49 89 460 24 03
info@elatec.de