

PVC Inlet



Mechanical dimensions	Diameter		Thickness mm		
	Φ25mm +/- 0.5mm		0.8mm		
	Φ27mm +/- 0.5mm		0.8mm		
		Φ30mm +/- 0.5mm		0.8mm	
Chip type		EM4100, Hitag series, Atmel 5557, Mifare Series, I-code SLI			
Electrical	Operating frequency	125kHz	+/-6kHz		
	Operating frequency	14MHz	+/-500kHz		
Temperature	Storage	-25°C to + 65°C			
	Operating	-25°C to + 65°C			
Material	PVC with copper wire antenna and module, IP65				
Options	adhesive backing, code printing				
Packaging	Delivered in shrink wrap and packed in cartons				
Type number	PVCII-XX-YY (XX= Chip, YY= Diameter)				

Datenblatt Datasheet

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, IDentification Systems
 Max-Planck-Str. 16, D-82223 Eichenau, GERMANY
 Phone: +49 8141 53498-0
 Fax: +49 8141 53498-29
RFID@elatec.de

Elatec Vertriebs GmbH
 Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY
 Phone: +49 89 46 23 070 ;
 Fax: +49 89 46 23 07 99
info@elatec.de