

Wristband



Features	Available in different colours Water Proof and Easy to wear		
Chip type	H4100,H4120,EM4450,TK4100,T5557,Hitag1,Hitag2,HitagS Mifare1 S50,Mifare1 S70,Ultralight,Mifare Desfire ICODE SLI SI2,ICODE 1		
Electrical	Operating frequency	125kHz	+/-6kHz
	Operating frequency	14MHz	+/-500kHz
Temperature	-10°C to +50°C		
Material	ABS		
Options	Printable with silk screen & offset printing on PVC disc tag Available with ink jet numbering print		

Elatec reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. Elatec declines all responsibility for the use of product with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Elatec GmbH, Identification Systems
 Max-Planck-Str. 16, D-82223 Eichenau, GERMANY
 Phone: +49 8141 53498-0
 Fax: +49 8141 53498-29
RFID@elatec.de

Elatec Vertriebs GmbH
 Hans-Pinsel-Str. 10b, D-85540 Haar, GERMANY
 Phone: +49 89 46 23 070 ;
 Fax: +49 89 460 24 03
info@elatec.de